

Easy to use, creative, stylish design





IK41VE1-M2M version

Design

Dimensions: 88x27.4x11.45mm

Weight: 32g

Colors available: white/ black

External interface

Form-Factor: USB Dongle, (Type A) LED: Power, Network, 1 red/ 1 green/ 1 blue

1 x 3FF

Power: Powered via USB interface

Connectivity

FDD LTE Band 1/3/7/8/20/28 UMTS/HSPA/HSPA+ Band 1/8 GSM/EDGE/GPRS: 850/900/1800/1900MHz

Network: TDD LTE, FDD LTE, DC

HSPA+,HSPA+,HSUPA,HSDPA,UMTS,EDGE,GPRS

Support "PC<->Device" connectivity, works via USB 3G/2G Main Antenna 2X2 MIMO 3G RX Diversity Antenna, support UMTS band Support 2(TS9) (optional in PCBA), no interface in general casing.

Data speed:

EDGE: up to 237Kbps Download up to 118Kbps Upload Class 12 GPRS: up to 85.6Kbps Download up to 42.8Kbps Upload Class 12 HSUPA: Yes, DL Category 10, 14.4Mbps; UL, cat 6, 5.76Mbps; 3GPP R6 HSPA+: Yes, DL Category 14, 21Mbps; UL, cat 6,5.76Mbps; 3GPP R7 DC HSPA+: Yes, cat24 DL 42Mbps; UL 23Mbps; 3GPP R9 FDD LTE: Yes, Cat 4, DL 150Mbps, UL 50Mbps, 3GPP R10 TDD LTE: Yes, Cat 4, DL 112Mbps, UL 10Mbps, 3GPP R10 Configuration Interface: AT command. Local upgrade. FOTA (Alcatel FOTA)

Other Features

SIM LOCK can be customized USSD can be customized Support under administrator SMS Support Statistic Support IPV4 and IPV6 agreement.

Hardware Features

Platform: Qualcomm MDM9207 Internal Storage: 2Gb NAND flash + 1Gb LPDDR2

Certifications

CE RoHS V3 REACH WEEE WHOL

In Box

Quick Start Guide Hotline Leaflet(Default not, can be customized) User manual (Software Version, embedded in the dongle)



