

LINKKEY

LTE Cat4 USB Dongle

Easy to use, creative, stylish design



IK41VE1-WEBUI version

Design

Dimensions: 88x27.4x11.45mm
Weight: 32g
Colors available: white/ black

External interface

Form-Factor: USB Dongle, (Type A)
LED: Power, Network, 1 red/ 1 green/ 1 blue
1 x 3FF
Power: Powered via USB interface

Connectivity

FDD LTE Band 1/3/7/8/20/28
UMTS/HSPA/HSPA+ Band 1/8
GSM/EDGE/GPRS: 850/900/1800/1900MHz
Network: TDD LTE, FDD LTE, DC
HSPA+,HSPA+,HSUPA,HSDPA,UMTS,EDGE,GPRS

Support "PC<->Device"connectivity, works via USB
3G/2G Main Antenna 2X2 MIMO
3G RX Diversity Antenna, support UMTS band
Support 2(TS9)(optional in PCBA), no interface in general casing.

Data speed:
EDGE: up to 237Kbps Download up to 118Kbps Upload Class 12
GPRS: up to 85.6Kbps Download up to 42.8Kbps Upload Class 12
HSUPA: Yes, DL Category 10, 14.4Mbps; UL, cat 6, 5.76Mbps; 3GPP R6
HSPA+ : Yes, DL Category 14, 21Mbps; UL, cat 6.5.76Mbps; 3GPP R7
DC HSPA+: Yes, cat24 DL 42Mbps; UL 23Mbps; 3GPP R9
FDD LTE: Yes, Cat 4,DL 150Mbps, UL 50Mbps, 3GPP R10
TDD LTE: Yes, Cat 4, DL 112Mbps, UL 10Mbps, 3GPP R10
Configuration Interface: [Web UI](#), Local upgrade, FOTA (Alcatel FOTA)

Other Features

SIM LOCK can be customized
USSD can be customized
Support under administrator SMS
[Welcome page](#)
Support Statistic
Support IPV4 and IPV6 agreement.

Hardware Features

Platform: Qualcomm MDM9207
Internal Storage: 2Gb NAND flash + 1Gb LPDDR2

Certifications

CE
RoHS V3
REACH
WEEE
WHQL

In Box

Quick Start Guide
Product Safe Information
Hotline Leaflet(Default not, can be customized)
User manual (Software Version, embedded in the dongle)

